## HTS101 XP

## TANNOY

# Bringing movies to life



## Blockbuster sound, bijou sound system

From the box office to your living room, Tannoy's HTS101 XP Home Theatre System brings movies to life. This innovative 5.1 loudspeaker package improves on the original multi-award winning HTS101, delivering enhanced detailed effects and crystal clear dialogue. With additional subwoofer power you'll get cinematic scale like no other loudspeaker package at its price. In the home, this complete home theatre speaker set up is compact, discreetly finished, and easy to place. From action and adventure to intense drama, HTS101 XP is the best supporting role for any movie.

#### The HTS Satellites

Directed by Tannoy's lead engineering team, HTS Satellites draw heavily on Tannoy's coaxial driver know-how and world renowned acoustic expertise. Each unit uses an elliptical driver with coaxially mounted tweeter in a solid wood speaker enclosure. The result is Tannoy's famous point source clarity and an exceptionally detailed sound with rich tones and high power handling. Supplied as five identical loudspeakers that can be positioned vertically or horizontally, each HTS Satellite is produced with a a blend of brushed textured vinyl panels and gloss black end caps. Concealed wall mounting brackets are supplied for discreet installation.

#### The HTS101 XP Subwoofer

Deep bass is a critical component of an award winning sound mix. Tannoy's TS2.8 Subwoofer plays a starring role here, providing eXtra Power (XP), and producing room filling low frequency effects from a compact and easy to place design. At its heart is a high efficiency digital amplifier outputting a genuine 180 Watts RMS. A sophisticated digital signal processing (DSP) engine optimises bass output to the 200 mm (8") long-throw driver, which works in conjunction with a mass-loaded 200 mm (8") auxiliary bass radiator (ABR). The result is a small, independent subwoofer with flexible controls that delivers.

Compatible with the widest range of AV amplifiers and receivers, HTS101 XP is ideal for stereo and all 5.1 channel surround sound formats.

#### HTS: Bringing movies to life.





### Specifications

PERFORMANCE	HTS101 XP Satellite -	PERFORMANCE	TS2.8 Subwoofer
Recommended amplifier power (Watts RMS)	25 - 100	Amplifier output power (Watts RMS)	180
Sensitivity (2.82 Volts @ 1m)	89 dB	Low frequency roll off	34 Hz
Nominal impedance (Ohms)	8	(-6 dB, typical in room) Crossover frequency	50 - 150 Hz variable, 2 <sup>nd</sup> order
Frequency response (-6 dB)	100 Hz – 43 kHz		50 - 150 Hz valiable, 2 ° Older
DRIVE UNITS			
Co-axial high frequency	20 mm (0.78") titanium WideBand™ dome, with neodymium magnet system	Low frequency	200 mm (8"), long throw side firing woofer 200 mm (8"), long throw auxiliary bass radiator (ABR)
Co-axial low frequency	100 x 65 mm (4 x 2.5" elliptical paper cone)	Magnetic shielding	No
Magnetic shielding	No	AMPLIFIER	
CROSSOVER		Protection systems	Over temperature, switch on/off transient, over current, over-drive (clipping compressor)
Crossover frequency	3 kHz (LF to HF)	Input connections	Phono (RCA) LFE and stereo left & right
CONSTRUCTION		User controls	Volume, crossover frequency, phase (0-180°, switchable), mode (auto/always on), mains on/off
Cabinet construction & finish	MDF with black brushed vinyl and high gloss end caps	Power supply voltage	100 - 120 V / 220 - 240 V (switchable) 50 - 60 Hz
Dimensions (H x W x D)	185 x 100 x 109 mm	Rated maximum power consumption	200 Watts
(excl grille)	(7.3 × 4.0 × 4.3")	Mains fuse	100 - 120 VAC T6.3 AL 250 V /
Net weight	1.4 kg (3.1 lbs)	CONSTRUCTION	220 - 240 VAC T3.15AL 250 V
		Cabinet construction & finish	MDF with black brushed vinyl
		Dimensions (H x W x D) (incl. feet)	320 x 324.2 x 270 mm (12.6 x 12.8 x 10.6")

Net weight

8.6 kg (19 lbs)

tannoy.com