

**Klipsch**

*Outdoor*

**SPEAKERS**



# ALL-WEATHER SERIES

When you want to listen to your favorite music by the pool or want to provide background music while you entertain guests on your patio, our line of outdoor speakers has you covered. The Klipsch All-Weather loudspeaker line delivers clear, dynamic performances while providing more sound per watt than comparably sized speakers, allowing for better sound coverage in a smaller package.



- Paintable, UV-resistant ABS enclosure with rustproof aluminum grille
- Supplied with C-style mounting bracket and stainless steel hardware

## AW-650 6.5" ALL-WEATHER SPEAKER

<b>FREQUENCY RESPONSE</b>	70Hz-20KHz +/- 3dB
<b>SENSITIVITY</b>	95dB @ 2.83V/1 meter
<b>IMPEDANCE</b>	8 ohms compatible
<b>CROSSOVER FREQUENCY</b>	3400Hz
<b>POWER HANDLING (CONT/PEAK)</b>	75W /300W
<b>HIGH FREQUENCY DRIVER</b>	1" (2.5 cm) titanium dome tweeter with a 90° x 90° Tractrix Horn
<b>LOW FREQUENCY DRIVER</b>	6.5" (16.5cm) IMG woofer
<b>DIMENSIONS</b>	15" (38.1cm) H x 9.5" (21.4cm) W x 11" (27.9) cm) D
<b>WEIGHT</b>	9 lbs (4.1 kg)
<b>FINISH</b>	Black or White enclosure and grille

**SHIPPING QUANTITY:** Pair  
**SHIPPING WEIGHT:** 11.8 kg  
 26 lbs

PART NUMBER
1009316 (Black)
097093000001 (White)

**NOTES:**



- Paintable, UV-resistant ABS enclosure with rustproof aluminum grille
- Supplied with C-style mounting bracket and stainless steel hardware

## AW-525 5.25" ALL-WEATHER SPEAKER

<b>FREQUENCY RESPONSE</b>	80Hz-20KHz +/- 3dB
<b>SENSITIVITY</b>	94dB @ 2.83V/1 meter
<b>IMPEDANCE</b>	8 ohms compatible
<b>CROSSOVER FREQUENCY</b>	2450Hz
<b>POWER HANDLING (CONT/PEAK)</b>	75W /300W
<b>HIGH FREQUENCY DRIVER</b>	1" (2.5 cm) titanium dome tweeter with a 90° x 90° Tractrix Horn
<b>LOW FREQUENCY DRIVER</b>	5.25" (13.3cm) IMG woofer
<b>DIMENSIONS</b>	11.8" (30cm) H x 8" (20.3cm) W x 9" (22.9 cm) D
<b>WEIGHT</b>	6.5 lbs (3kg)
<b>FINISH</b>	Black or White enclosure and grille

**SHIPPING QUANTITY:** Pair  
**SHIPPING WEIGHT:** 8.1 kg  
 18 lbs

PART NUMBER
1009313 (Black)
097090000001 (White)

**NOTES:**



- Quick, easy installation
- Multipurpose design

## CP-6 5.25" COMPACT HIGH PERFORMANCE SPEAKER

<b>FREQUENCY RESPONSE</b>	70Hz-22KHz +/- 3dB
<b>SENSITIVITY</b>	94dB @ 2.83V/1 meter
<b>IMPEDANCE</b>	8 ohms compatible
<b>CROSSOVER FREQUENCY</b>	3000Hz
<b>POWER HANDLING (CONT/PEAK)</b>	75W /300W
<b>HIGH FREQUENCY DRIVER</b>	.75" (1.9cm) aluminum dome tweeter with a 90° x 90° Tractrix Horn
<b>LOW FREQUENCY DRIVER</b>	5.25" (13.3cm) long-throw IMG woofer
<b>TERMINALS</b>	Front baffle mounted accessed via rear pull-through
<b>DIMENSIONS</b>	11.0" (27.9cm) H x 7.0" (17.8cm) W x 6.1" (15.5cm) D
<b>MOUNTING DEPTH</b>	6.9" (17.5cm) D
<b>WEIGHT</b>	5.8 lbs (2.6kg)
<b>FINISH</b>	Black or White enclosure and grille

**SHIPPING QUANTITY:** Pair  
**SHIPPING WEIGHT:** 7.8 kg  
 17.19 lbs

PART NUMBER
1016297 (Black)
1060387 (White)

**NOTES:**



- Paintable, UV-resistant ABS enclosure with rustproof aluminum grille
- Supplied with C-style mounting bracket and stainless steel hardware

## AW-400 4" ALL-WEATHER SPEAKER

<b>FREQUENCY RESPONSE</b>	91Hz-20kHz +/- 3dB
<b>SENSITIVITY</b>	91dB @ 2.83V/1 meter
<b>IMPEDANCE</b>	8 ohms compatible
<b>CROSSOVER FREQUENCY</b>	2940Hz
<b>POWER HANDLING (CONT/PEAK)</b>	50W /200W
<b>HIGH FREQUENCY DRIVER</b>	1" (2.5 cm) titanium dome tweeter with a 90° x 90° Tractrix Horn
<b>LOW FREQUENCY DRIVER</b>	4" (10.2cm) IMG woofer
<b>DIMENSIONS</b>	9.5" (24.1cm) H x 6.5" (16.5cm) W x 7.25" (18.4 cm) D
<b>WEIGHT</b>	5 lbs (2.3 kg)
<b>FINISH</b>	White enclosure and grille

**SHIPPING QUANTITY:** Pair  
**SHIPPING WEIGHT:** 5.5 kg  
 12.1 lbs

**PART NUMBER**  
 09708500001

**NOTES:**

## PROFESSIONAL SERIES LANDSCAPE SPEAKERS

The new Klipsch Landscape Series is a horn-loaded, all-weather, durable, low-distortion, high-efficiency system - designed from the ground up with 70 years of high-performance audio experience by one of the most legendary and reliable audio companies in the world.

- Landscape Satellites and Subwoofers for full-range outdoor performance • 70V/100V/8 Ohm compatibility
- UV-resistant enclosures



- All-new custom Tractrix® Horn provides ultra-wide 105° horizontal dispersion
- 50 watt, 70V/100V multi-tap transformer with 8-ohm bypass
- All-weather durability - IP45 rating

## PRO-650T-LS 6.5" LANDSCAPE SATELLITE

<b>FREQUENCY RANGE</b>	100Hz - 24kHz +/- 3dB 92Hz - 30kHz +/- 6dB 77Hz - 35kHz +/- 10dB
<b>HIGH FREQUENCY DRIVER</b>	1" (2.54cm) Aluminum Dome Tweeter mated to an all new 105° custom Tractrix® horn
<b>LOW FREQUENCY DRIVER</b>	6.5" (16.51cm) IMG Woofer
<b>SENSITIVITY</b>	90 dB @ 2.83V/1 meter
<b>COVERAGE ANGLE</b>	105°
<b>POWER HANDLING</b>	100W Peak
<b>70V / 100V TAP SETTINGS</b>	70V: 6.25W, 12.5W, 25W, 50W 100V: 12.5W, 25W, 50W 8 Ohm Bypass
<b>ENCLOSURE MATERIAL</b>	UV Treated, Glass-Filled ABS Cabinet
<b>FINISH</b>	Brown Matte, Paintable
<b>PRODUCT DIMENSIONS</b>	8.27" x 8.82" x 11.02" (210mm x 224mm x 280mm)
<b>PRODUCT WEIGHT</b>	7 lbs (3.18 kg)
<b>ACCESSORIES</b>	PRO-18-GS 18" Ground Stake (PN: 1063448) (sold separately)

**SHIPPING QUANTITY:** Single  
**SHIPPING WEIGHT:** 4.5 kg  
 10 lbs

**PART NUMBER**  
 1063139

**NOTES:**



- All-new custom Tractrix® Horn provides ultra-wide 105° horizontal dispersion
- 50 watt, 70V/100V multi-tap transformer with 8-ohm bypass
- All-weather durability - IP45 rating

## PRO-500T-LS 5" LANDSCAPE SATELLITE

<b>FREQUENCY RANGE</b>	130Hz - 30kHz +/- 3dB 113Hz - 32kHz +/- 6dB 93Hz - 36kHz +/- 10dB
<b>HIGH FREQUENCY DRIVER</b>	1" (2.54cm) Aluminum Dome Tweeter mated to an all new 105° custom Tractrix® horn
<b>LOW FREQUENCY DRIVER</b>	5" (12.7cm) IMG Woofer
<b>SENSITIVITY</b>	88 dB @ 2.83V/1 meter
<b>COVERAGE ANGLE</b>	105°
<b>POWER HANDLING</b>	60W Peak
<b>70V / 100V TAP SETTINGS</b>	70V: 3.75W, 7.5W, 15W, 30W 100V: 7.5W, 15W, 30W 8 Ohm Bypass
<b>ENCLOSURE MATERIAL</b>	UV Treated, Glass-Filled ABS Cabinet
<b>FINISH</b>	Brown Matte, Paintable
<b>PRODUCT DIMENSIONS</b>	6.3" x 6.85" x 8.5" (160mm x 174mm x 216mm)
<b>PRODUCT WEIGHT</b>	5 lbs (2.27 kg)
<b>ACCESSORIES</b>	PRO-10-GS 10" Ground Stake (PN: 1063447) (sold separately)

**SHIPPING QUANTITY:** Single  
**SHIPPING WEIGHT:** 3.6 kg  
 8 lbs

**PART NUMBER**  
 1063137

**NOTES:**



- Long-throw 12" IMG woofer
- Dual voice coil design for transformerless 70V/100V/8 Ohm compatibility
- All-weather durability - IP45 rating

### PRO-12SW-LS 12" DIRECT BURIAL SUBWOOFER

<b>FREQUENCY RANGE</b>	34Hz -100Hz +/- 3dB 29Hz -110Hz +/- 6dB 25Hz -125Hz +/- 10dB
<b>SYSTEM TYPE</b>	Band Pass Full Burial
<b>WOOFER</b>	12" (30.48cm) IMG Dual Voice Coil
<b>SENSITIVITY</b>	90 dB @ 2.83V/1 meter
<b>POWER HANDLING</b>	250W
<b>IMPEDANCE</b>	70V @ 300W (Transformerless) 8 Ohm Stereo 4 Ohm Mono
<b>ENCLOSURE MATERIAL</b>	Canopy: Rustproof, UV Resistant Aluminum Cabinet: Heavy Duty, High Impact Polyethylene
<b>FINISH</b>	Canopy: Metallic Brown, Paintable Cabinet: Matte Black, Paintable
<b>PRODUCT DIMENSIONS</b>	25" x 16.14" x 26.42" (635mm x 410mm x 671mm)
<b>PRODUCT WEIGHT</b>	55 lbs (25 kg)

**SHIPPING QUANTITY:** Single  
**SHIPPING WEIGHT:** 34 kg  
75 lbs

**PART NUMBER**  
1063141

**NOTES:**



- Long-throw 10" IMG woofer
- Dual voice coil design for transformerless 70V/100V/8 Ohm compatibility
- All-weather durability - IP45 rating

### PRO-10SW-LS 10" HALF BURIAL SUBWOOFER

<b>FREQUENCY RANGE</b>	47Hz -103Hz +/- 3dB 40Hz -110Hz +/- 6dB 33Hz -123Hz +/- 10dB
<b>SYSTEM TYPE</b>	Band Pass Half Burial
<b>WOOFER</b>	10" (25.4cm) IMG Dual Voice Coil
<b>SENSITIVITY</b>	90 dB @ 2.83V/1 meter
<b>POWER HANDLING</b>	200W
<b>IMPEDANCE</b>	70V @ 250W (Transformerless) 8 Ohm Stereo 4 Ohm Mono
<b>ENCLOSURE MATERIAL</b>	Canopy: Rustproof, UV Resistant Aluminum Cabinet: Heavy Duty, High Impact Polyethylene
<b>FINISH</b>	Canopy: Metallic Brown, Paintable Cabinet: Matte Black, Paintable
<b>PRODUCT DIMENSIONS</b>	21.85" x 16.10" x 16.10" (555mm x 409mm x 409mm)
<b>PRODUCT WEIGHT</b>	35 lbs (15.91 kg)

**SHIPPING QUANTITY:** Single  
**SHIPPING WEIGHT:** 22.6 kg  
50 lbs

**PART NUMBER**  
1063140

**NOTES:**

## ACCESSORIES



### PRO-18-GS 18" GROUND STAKE

<b>MATERIAL</b>	Ground Stake: Glass-Filled (25%) ABS Security Plate: Galvanized Stamped Steel
<b>INCLUDED IN-BOX</b>	18" Ground Stake, 7" Security Plate, Installation Manual
<b>FINISH</b>	Brown Matte, Paintable
<b>PRODUCT DIMENSIONS</b>	17.99" x 3.35" x 3.35" (457mm x 85mm x 85mm)
<b>PRODUCT WEIGHT</b>	2 lbs (0.91 kg)
<b>RECOMMENDED FOR USE WITH</b>	PRO-650T-LS 6.5" Landscape Satellite (PN: 1063139)

**SHIPPING QUANTITY:** Single  
**SHIPPING WEIGHT:** 1.3 kg  
3 lbs

**PART NUMBER**  
1063448

**NOTES:**



### PRO-10-GS 10" GROUND STAKE

<b>MATERIAL</b>	Ground Stake: Glass-Filled (25%) ABS Security Plate: Galvanized Stamped Steel
<b>INCLUDED IN-BOX</b>	10" Ground Stake, 7" Security Plate, Installation Manual
<b>FINISH</b>	Brown Matte, Paintable
<b>PRODUCT DIMENSIONS</b>	11.81" x 3.35" x 3.35" (300mm x 85mm x 85mm)
<b>PRODUCT WEIGHT</b>	2 lbs (0.91 kg)
<b>RECOMMENDED FOR USE WITH</b>	PRO-500T-LS 5" Landscape Satellite (PN: 1063137)

**SHIPPING QUANTITY:** Single  
**SHIPPING WEIGHT:** 1.3 kg  
3 lbs

**PART NUMBER**  
1063447

**NOTES:**

NEW



## PRO-1-SM

<b>FOR USE WITH</b>	PRO-500T-LS (1063137) and PRO-650T-LS (1063139)
<b>CONSTRUCTION</b>	Rustproof aluminum parts with stainless steel hardware
<b>MAXIMUM PITCH</b>	45° up, 90° down
<b>PITCH INCREMENTS</b>	15°
<b>MAXIMUM PAN</b>	100° clockwise, 100° counterclockwise
<b>WEIGHT</b>	1.2 lbs / .54 kg
<b>DIMENSIONS</b>	1.68" x 11.12" x 4.13" (4.3cm x 29.5cm x 10.5cm)
<b>PACKED AS</b>	Eaches
<b>FINISH</b>	Satin Black
<b>ACCESSORIES (NOT INCLUDED)</b>	5/16" Washers (2) and Mounting Hardware 1" Tree Strap Square U-Bolt for Pole Mounting (1.25" Minimum Width)

**SHIPPING QUANTITY:** Single  
**SHIPPING WEIGHT:** 10 lbs

PART NUMBER
1063139

**NOTES:**

## PROFESSIONAL SERIES ROCK SPEAKERS

With IMG woofers and Tractrix horn-loaded Aluminum Dome Tweeters, the Pro Series rock speakers use the same high performance acoustic design philosophies of our legendary indoor products, bringing the world's most dynamic, powerful, detailed sound to your outdoor living space. From small residential systems to massive commercial installs, the Klipsch Pro Series rock speakers are designed to make any installation job quick and easy. For distributed line application, the Pro Series rock speakers feature a 70V/100V multi-tap transformer with 8 ohm bypass, allowing for exceptional balance at any listening location - all selectable from an easily accessible, tool-free rotary switch on the back of the speaker.

- Rock satellites and subwoofer for full-range outdoor performance • 70V/100V/8 Ohm compatibility
- UV-resistant enclosures



- Rock subwoofer speaker
- Dual voice coil design for transformerless 70V/100V capability with 8-ohm bypass
- UV-resistant, mechanically reinforced fiberglass cabinet

## PRO-10SW-RK 10" ROCK SUBWOOFER

<b>FREQUENCY RANGE</b>	47Hz - 103Hz +/- 3dB 40Hz - 110Hz +/- 6dB 33Hz - 123Hz +/- 10dB
<b>SYSTEM TYPE</b>	Sealed box
<b>WOOFER</b>	10" (25.4cm) IMG Dual Voice Coil
<b>SENSITIVITY</b>	90 dB @ 2.83V/1 meter
<b>POWER HANDLING</b>	200W
<b>IMPEDANCE</b>	70V @ 250W (Transformerless) 8 Ohm Stereo 4 Ohm Mono
<b>ENCLOSURE MATERIAL</b>	UV Treated Fiberglass
<b>FINISH</b>	Granite or Sandstone
<b>PRODUCT DIMENSIONS</b>	13.39" x 18.43" x 20.67" (340mm x 468mm x 525mm)
<b>PRODUCT WEIGHT</b>	30 lbs (13.6 kg)

**SHIPPING QUANTITY:** Single  
**SHIPPING WEIGHT:** 16 kg  
35.4 lbs

PART NUMBER
1063232 (Granite)
1063231 (Sandstone)

**NOTES:**



- All-new custom Tractrix® Horn provides ultra-wide 105° horizontal dispersion
- 70V/100V multi-tap transformer with 8-ohm bypass
- UV-resistant, mechanically reinforced fiberglass cabinet

### PRO-650T-RK 6.5" 2-WAY ROCK SATELLITE

<b>FREQUENCY RANGE</b>	100Hz - 24kHz +/- 3dB 92Hz - 30kHz +/- 6dB 77Hz - 35kHz +/- 10dB
<b>HIGH FREQUENCY DRIVER</b>	1" (2.54cm) Aluminum Dome Tweeter mated to an all new 105° custom Tractrix® horn
<b>LOW FREQUENCY DRIVER</b>	6.5" (16.51cm) IMG Woofer
<b>SENSITIVITY</b>	90 dB @ 2.83V/1 meter
<b>COVERAGE ANGLE</b>	105°
<b>POWER HANDLING</b>	100W Peak
<b>70V / 100V TAP SETTINGS</b>	70V: 6.25W, 12.5W, 25W, 50W 100V: 12.5W, 25W, 50W 8 Ohm Bypass
<b>ENCLOSURE MATERIAL</b>	UV Treated Fiberglass
<b>FINISH</b>	Granite or Sandstone
<b>PRODUCT DIMENSIONS</b>	10.91" x 9.65" x 13.43" (277mm x 245mm x 341mm)
<b>PRODUCT WEIGHT</b>	11 lbs (4.98 kg)

**SHIPPING QUANTITY:** Single  
**SHIPPING WEIGHT:** 6.6 kg  
14.7 lbs

PART NUMBER	
1063230 (Granite)	
1063229 (Sandstone)	

**NOTES:**



- All-new custom Tractrix® Horn provides ultra-wide 105° horizontal dispersion
- 70V/100V multi-tap transformer with 8-ohm bypass
- UV-resistant, mechanically reinforced fiberglass cabinet

### PRO-500T-RK 5" 2-WAY ROCK SATELLITE

<b>FREQUENCY RANGE</b>	130Hz - 30kHz +/- 3dB 113Hz - 32kHz +/- 6dB 93Hz - 36kHz +/- 10dB
<b>HIGH FREQUENCY DRIVER</b>	1" (2.54cm) Aluminum Dome Tweeter mated to an all new 105° custom Tractrix® horn
<b>LOW FREQUENCY DRIVER</b>	5" (12.7cm) IMG Woofer
<b>SENSITIVITY</b>	88 dB @ 2.83V/1 meter
<b>COVERAGE ANGLE</b>	105°
<b>POWER HANDLING</b>	60W Peak
<b>70V / 100V TAP SETTINGS</b>	70V: 3.75W, 7.5W, 15W, 30W 100V: 7.5W, 15W, 30W 8 Ohm Bypass
<b>ENCLOSURE MATERIAL</b>	UV Treated Fiberglass
<b>FINISH</b>	Granite or Sandstone
<b>PRODUCT DIMENSIONS</b>	9.21" x 9.72" x 10.43" (234mm x 247mm x 265mm)
<b>PRODUCT WEIGHT</b>	8 lbs (3.62 kg)

**SHIPPING QUANTITY:** Single  
**SHIPPING WEIGHT:** 5.1 kg  
11.2 lbs

PART NUMBER	
1063228 (Granite)	
1063227 (Sandstone)	

**NOTES:**