

Cabasse



IO2

SPATIALLY COHERENT WITH STYLE

Inspired by the famous Baltic line and based on the same principles of co-axial coincidence, the tiny spherical iO2 presents an unrivaled performance versus size ratio. In a living room or in a professional sound studio, in stereo as well as in multi-channel, this concentration of the Cabasse essence keeps on amazing through its explosive sonic presence and its discreet integration.

Cabasse



IO2



SPECIFICATIONS

	On stand	On base	In ceiling
Position	Floorstanding	On Bookshelf/ On wall	Recessed
Ways	2	2	2
Drivers	Coaxial midrange-tweeter: 13 cm Duocell - 2.7 cm dome Kaladex®	Coaxial midrange-tweeter: 13 cm Duocell - 2.7 cm dome Kaladex®	Coaxial midrange-tweeter: 13 cm Duocell - 2.7 cm dome Kaladex®
Cross-over point	2 700 Hz	2 700 Hz	2 700 Hz
Frequency response	150 - 22 000 Hz	150 - 22 000 Hz	150 - 22 000 Hz
Sensitivity 1 W / 1 m	93 dB	93 dB	93 db
Nominal Impedance	8 ohms	8 ohms	8 ohms
Minimum Impedance	3,8 ohms	3,8 ohms	3,8 ohms
Power Handling	80 W	80 W	80 W
Peak Power	580 W	580 W	580 W
Magnetic shielding	Yes	No	-
Dimensions (h x w x d)	112 x 33 x 33 cm	Ø 16 cm	Ø 26 cm
Weight	15 Kg	1,8 Kg	1,9 Kg
Finishes	Light Oak / Glossy Black Light Oak / Glossy White Wenge/ Glossy Black Wenge/ Glossy White	Glossy Black, glossy White	White



Cabasse SAS – 210 rue René Descartes – BP10 – 29280 Plouzané – Tél +33 (0)2 98 05 88 88 - Fax +33 (0)2 98 05 88 99
www.cabasse.com

Due to technical improvements already under way in our constant search for optimum quality, Cabasse reserves the right to modify all the models presented in specification sheets, advertising materials and manuals without prior notice.