

THX[®]

ULTRA2[™]



Don't say we didn't warn you

Once you hear it, you'll have to have it

THX® CINEMA SERIES

This extraordinary custom home theater series brings cinema-quality sound to the comforts of home by using Klipsch's renowned, professional-grade technology. These THX Ultra and Select certified speakers expertly deliver the raw explosiveness and fine detail of any film format and will shatter your expectations for home theater performance. The flat magnetic grille allows these in-wall and in-ceiling speakers to melt seamlessly into your home theater.

• THX Certified for high performance home cinema • THX Ultra and THX Select Certified models



- THX Ultra Certified in-wall LCR speaker for rooms over 3000 cubic feet
- Cinema quality sound in an architectural format
- Fully enclosed back box
- Flat, magnetic, paintable grille



- THX Ultra Certified in-wall surround speaker for rooms over 3000 cubic feet
- Cinema quality sound in an architectural format
- Fully enclosed back box
- Wide Dispersion Sound Technology (WDST)
- Flat, magnetic, paintable grille



- THX Ultra Certified in-wall LCR speaker for rooms over 3000 cubic feet
- Cinema quality sound in an architectural format
- Fully enclosed back box
- Flat, magnetic, paintable grille

THX-8000-L 8" IN-WALL LCR SPEAKER

FREQUENCY RESPONSE	80Hz-23kHz +/- 3dB
SENSITIVITY	91dB @ 2.83V/1 meter
IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2300Hz
POWER HANDLING (CONT/PEAK)	150W /600W
HIGH FREQUENCY DRIVER	1" (2.54cm) Titanium dome compression driver mated to 80° x 80° Tractrix Horn
LOW FREQUENCY DRIVER	8" (20cm) Aluminum Cone Woofer
DIMENSIONS	20.63" (52.4cm) H x 11.63" (29.54cm) W
MOUNTING DEPTH	3.88" (9.85cm)
CUTOUT DIMENSIONS	19.13" (48.59cm) H x 10.12" (25.7cm) W
WEIGHT	17.5 lbs. (7.9kg)
INSTALLATION KIT	IK-802-W (sold separately)

THX-8000-S 8" IN-WALL SURROUND SPEAKER

FREQUENCY RESPONSE	80Hz-20kHz +/- 3dB
SENSITIVITY	90dB @ 2.83V/1 meter
IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2130Hz
POWER HANDLING (CONT/PEAK)	100W /400W
HIGH FREQUENCY DRIVER	Two 1" (2.5cm) Titanium dome neodymium tweeters in a diffuse Tractrix horn array
LOW FREQUENCY DRIVER	8" (20cm) Aluminum Cone Woofer
DIMENSIONS	20.63" (52.4cm) H x 11.63" (29.54cm) W
MOUNTING DEPTH	3.88" (9.85cm)
CUTOUT DIMENSIONS	19.13" (48.59cm) H x 10.12" (25.7cm) W
WEIGHT	17.5 lbs. (7.9kg)
INSTALLATION KIT	IK-802-W (sold separately)

THX-5002-L DUAL 5.25" IN-CEILING LCR SPEAKER

FREQUENCY RESPONSE	45Hz-20kHz +/- 3dB
SENSITIVITY	93dB @ 2.83V/1 meter
IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	1200 Hz & 1800 Hz
POWER HANDLING (CONT/PEAK)	100W /400W
HIGH FREQUENCY DRIVER	1" (2.5cm) Titanium tweeter in a 7.5 x 3.75" 60-90-110 VCT 45° Skewed horn
LOW FREQUENCY DRIVER	Two 5.25" (16.51cm) Cerametallic Woofers
DIMENSIONS	Ø14.89" (37.82cm)
MOUNTING DEPTH	9.23" (23.44cm)
CUTOUT DIMENSIONS	Ø13.39" (34.01cm)
WEIGHT	12 lbs (5.4kg)
INSTALLATION KIT	IK-502-C (sold separately)

SHIPPING QUANTITY: Single

SHIPPING WEIGHT: 9 kg
19.9 lbs

PART NUMBER

1066109



NOTES:

SHIPPING QUANTITY: Single

SHIPPING WEIGHT: 8.57 kg
18.9 lbs

PART NUMBER

1066110



NOTES:

SHIPPING QUANTITY: Single

SHIPPING WEIGHT: 7.2 kg
15.9 lbs

PART NUMBER

1066119



NOTES:



- THX Ultra Certified in-ceiling surround speaker for rooms over 3000 cubic feet
- Cinema quality sound in an architectural format
- Fully enclosed back box
- Wide Dispersion Sound Technology (WDST)
- Flat, magnetic, paintable grille

THX-5002-S DUAL 5.25" IN-CEILING SURROUND SPEAKER

FREQUENCY RESPONSE	45Hz-20kHz +/- 3dB
SENSITIVITY	93dB @ 2.83V/1 meter
IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2500Hz
POWER HANDLING (CONT/PEAK)	100W /400W
HIGH FREQUENCY DRIVER	Two 1" Titanium tweeters in vertically stacked Tractrix horns
LOW FREQUENCY DRIVER	Two 5.25" (16.51cm) Cerametallic Woofers
DIMENSIONS	Ø 14.89" (37.82cm)
MOUNTING DEPTH	9.23" (23.44cm)
CUTOUT DIMENSIONS	Ø 13.39" (34.01cm)
WEIGHT	11 lbs. (5.0kg)
INSTALLATION KIT	IK-502-C (sold separately)

SHIPPING QUANTITY: Single
SHIPPING WEIGHT: 6.3 kg
 13.9 lbs
PART NUMBER
 1066125



NOTES:



- THX Select Certified in-wall speaker for rooms up to 2000 cubic feet
- Cinema quality sound in an architectural format
- Flat, magnetic, paintable grille

THX-504-L QUAD 5.25" IN-WALL SPEAKER

FREQUENCY RESPONSE	46Hz-20kHz +/- 3dB
SENSITIVITY	92dB @ 2.83V/1 meter
IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	250 Hz & 2100 Hz
POWER HANDLING (CONT/PEAK)	150W /600W
HIGH FREQUENCY DRIVER	1" (2.54cm) Titanium diaphragm compression driver mated to 90° x 90° square Tractrix Horn
LOW FREQUENCY DRIVER	Four 5.25" (13.3cm) high-output, fiberglass cone woofers
DIMENSIONS	28.88" (73.35cm) H x 8.13" (20.65cm) W
MOUNTING DEPTH	3.52" (8.94cm)
CUTOUT DIMENSIONS	27.24" (69.19cm) H x 6.5" (16.51cm) W
WEIGHT	18.3 lbs (8.3kg)
INSTALLATION KIT	IK-504-W (sold separately)

SHIPPING QUANTITY: Single
SHIPPING WEIGHT: 9 kg
 19.9 lbs
PART NUMBER
 1066127



NOTES:



- THX Select Certified in-wall speaker for rooms up to 2000 cubic feet
- Cinema quality sound in an architectural format
- Flat, magnetic, paintable grille

THX-502-L DUAL 5.25" IN-WALL SPEAKER

FREQUENCY RESPONSE	46Hz-20kHz +/- 3dB
SENSITIVITY	92dB @ 2.83V/1 meter
IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2100Hz & 1200Hz
POWER HANDLING (CONT/PEAK)	100W /400W
HIGH FREQUENCY DRIVER	1" (2.54cm) Titanium diaphragm compression driver mated to 90° x 90° square Tractrix Horn
LOW FREQUENCY DRIVER	Dual 5.25" (13.3cm) high-output, fiberglass cone woofers
DIMENSIONS	17.98" (45.66cm) H x 8.11" (20.59cm) W
MOUNTING DEPTH	3.49" (8.86cm)
CUTOUT DIMENSIONS	16.42" (41.7cm) H x 6.57" (16.68cm) W
WEIGHT	9.6 lbs (4.4kg)
INSTALLATION KIT	IK-502-W or IK-502-W II (sold separately)

SHIPPING QUANTITY: Single
SHIPPING WEIGHT: 5.4 kg
 11.9 lbs
PART NUMBER
 1066128



NOTES: