IC 404 SLM



SPECIFICATIONS

FREQUENCY RESPONSE	91Hz - 20kHz
SENSITIVITY	88dB
POWER HANDLING	50W RMS / 200W Peak
NOMINAL IMPEDANCE	8 Ohm
HIGH FREQUENCY DRIVER	25mm (1″) Titanium Dome Tweeter
LOW FREQUENCY DRIVER	102mm (4″) Woven Synthetic Fiber HCC Cone
CUTOUT DIAMETER	211mm (8.3 in)
MOUNTING DEPTH	37mm (1.47 in)
PRODUCT DIAMETER	241mm (9.5 in)
PRODUCT WEIGHT	3.36kg (7.4 lbs)
INPUTS	Spring loaded binding posts
INSTALLATION KIT	RIK6.5SLM (Sold Separately)

Jamo

BIG SOUND, SLIM PACKAGE

One of the most compact in-ceiling speakers on the market, the IC 404 SLM features a shallow depth (50mm) with a fully enclosed back box. Along with premium acoustics straight from the legendary Jamo Custom 400 architectural series, the IC 404 SLM brings high performance acoustics in an extra slim package - for great sound where installation space is limited.

FIRE RATED BACK BOX

The ultra-slim galvanized metal back box provides a fire-rated enclosure for excellent sound isolation from neighboring floors, while ensuring consistent acoustics and exceptional low frequency response from a compact speaker.

PREMIUM ACOUSTICS

Featuring a 4" woven synthetic fiber woofer and a 1" titanium dome tweeter mated to a custom designed WaveGuide for dynamic, powerful low frequencies, and detailed, balanced highs - the IC 404 SLM brings classic Jamo sound to an ultra-slim package.

FLAT MAGNETIC GRILLE

The flat, magnetic, minimum bezel grille gives a modern, premium, and - most of all discreet look for great sound anywhere in the home without being obtrusive to the eye or interuptive of the design of the listening area. Square and round grilles are included to match any style.

COMPATIBLE WITH THE JAMO RIK6.5SLM

For increased mounting flexibility and preinstall marking during new construction.

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE ©2117 KLIPSCH GROUP, INC. JAMO IS A REGISTERED TRADEMARK OF KLIPSCH GROUP, INC. IN THE USA AND OTHER COUNTRIES A WHOLLY-OWNED SUBSIDIARY OF VOXX INTERNATIONAL CORPORATION. DOLBY ATMOS IS A REGISTERED TRADEMARK OF DOLBY LABORATORIES.