

Let us
entertain
you



Imagine that you can experience the amazing sound quality you hear in the best cinemas in the world – but in the comfort of your own home. The D 600 is the newest Jamo sound system that is built and approved to the same quality standards as the best movie theaters in the world namely THX. This highly advanced Jamo system meets the THX Ultra 2 standard, but is a truly musical hi-fi speaker system.

Consisting of carefully designed elements equipped with advanced technology, these speakers are not only able to reproduce the same powerful and detailed sound that you would only expect in real life or the best cinemas, but they are also able to present a sound stage that is as large in scale and physical appearance that it is hard to believe. The D 600 system is elegant and discreet, fashioned in a modern and graphic style that is able to blend in easily with the interiors in most modern homes.

State-of-the-Art technology

Jamo has developed driver units especially for this high end THX Ultra 2 system. Identical drivers used in both the LCR and surround speakers result in perfect balance across the speakers, and a 15"/1600W subwoofer equipped with Motional Feedback, ensures a dynamic, detailed and precise reproduction of even the lowest spectrum. The subwoofer is equipped with a unique touch interface which gives the user a variety of settings.

Specifications	D 600 SUB	Specifications	D 600 LCR	D 600 SUR
System	Active DSP based subwoofer, sealed enclosure. Motional feedback	System	3-Way Closed	3-Way Closed Dipole
User interface	Touch panel with backlight	Woofer (mm / in)	2 x 165 / 6½	1 x 165 / 6½
Woofer (mm / in)	380 / 15	Midrange (mm / in)	2 x 76 / 3	2 x 76 / 3
Rated power (Wrms)	600 @4ΩTHD+N <1%	Tweeter (mm / in)	25 / 1 DTT	2 x 25 / 1 DTT
Dynamic power (Wrms)	800 @4Ω	Power (W, long / short term)	200 / 300	150 / 200
Peak power (Wpk)	1600 @4Ω	Sensitivity (dB/2,8V/1m)	89	87
Maximum SPL (dB)	109	Frequency Range (Hz)	80 - 20.000	80 - 20.000
Frequency range (Hz)	20 - 200	Cross-over Frequency (Hz)	400 / 2.500	250 / 2.500
Variable cut off (Hz)	40 - 200	Impedance (Ohm)	4	4
Phase (deg.)	0 to -180	Weight (Kg / lb)	13 / 28.6	9 / 19.8
BGC	Variable	Dimension HxWxD (mm / in)	315 x 600 x 170 / 12.4 x 23.6 x 6.7	255 x 454 x 170 / 10 x 17.8 x 6.7
Line input	Yes, stereo pass through for daisy chain	Finish	Stone Grey	Stone Grey
LFE input	Yes, pass through for daisy chain			
Speaker level input	Yes			
Sensitivity (mVrms)	100			
Sound modes	Default. Personal. THX			
12V trigger	Yes, pass through for daisy chain.			
Mains switch	On / Off			
Voltage switch (fuse)	115V/60Hz (6.3A) / 230V/50Hz (3.15 A)			
Auto enable switch	Off / Auto / On			
Dimension (mm / in)	557 x 587 x 501 / 21.9 x 23.1 x 19.7			
Weight (kg / lb)	32 / 70.5			
Finish	Stone Grey			

Two D 600 SUB will meet THX Ultra2 output levels.
THX and theTHX logo are trademarks of THX Ltd.
which may be registered in some jurisdictions. All rights reserved.