- **Jamo**° F G II

IW 626 LCR FG II

3-WAY IN-WALL SPEAKER



SPECIFICATIONS

WOOFER (mm / in)	2 x 165 / 6 ½
MIDRANGE (mm / in)	38 / 1 ½
TWEETER (mm / in)	25 / 1 DTT
POWER (W LONG / SHORT TERM)	80 / 160
FREQUENCY RANGE (Hz)	55 – 22,000
IMPEDANCE (Ohm)	4 – 8 switchable
HOLE DIMENSION HxWxD (mm / in)	530 × 200 × 97 / 20.9 × 7.9 × 3.8
DIMENSIONS HxWxD (mm / in)	562 x 232 x 107 / 22.1 x 9.1 x 4.2
BACK BOX SIZE (Litre / in³)	22 / 1340
WEIGHT	3.5 / 7.7
FINISH	White (paintable)

ALL NEW PURE WHITE GRILLE

Redesigned magnetic, paintable grille with a new, more natural white color blends more seamlessly into the most premium of interior décor.

HIGH PERFORMANCE FRONT STAGE

Specially designed for front and center channels in a first-class home theater system, the dual woofer design provides great clarity and detail for dialogue and effects in movies. They can also be used in a premium 2-channel stereo system, and the midrange/tweeter module can rotate 90° for horizontal or vertical placement.

PREMIUM ACOUSTIC TECHNOLOGY

The dual 6.5" honeycomb fiberglass woofers, 1.5" silk dome midrange and 1" silk dome pivot tweeter provide balanced, dynamic, rich sound for your music and movies by utilizing core Jamo technologies:

- Decoupled Tweeter Technology (DTT)
 minimizes vibration transfer from the baffle
 to the tweeter, for detailed, clear high
 frequencies.
- WaveGuide provides focused, dynamic transfer of high frequencies into the listening space.
- Hard Conical Cone (HCC) minimizes woofer breakup for punchy, clear low frequencies.
- Centre Plug replaces traditional dust cap for cooler voice coil and higher power handling.

TWEETER ATTENUATION SWITCH

Cut high and mid frequencies on the fly with three-way attenuation switches (0, -3dB, -6dB) to custom tune the speaker to the listening space for smooth, detailed sound in any environment.

IMPEDANCE SELECTOR SWITCH

Custom tailor the speaker's impedance (4 ohm / 8 ohm) with the flip of a switch to optimize it to your amplifier or system.