

KRYPTON₉

The opinion of the lab

The KRYPTON 9 is the largest column in the range. Slim, elegant, almost discreet, it will nevertheless fill your space in a solid and concrete way.

About the technology...

The technical team has worked on each of the transducers to bring transparency and veracity to the sound message. The 13 cm diameter driver, composed of its Kevlar membrane (7th generation) and a machined metal dispersion ogive, ensures the reproduction of the medium frequencies. The new tweeter of the range, equipped with a rear decompression chamber and a 28 mm diameter impregnated fabric dome, takes care of the high frequencies (4000 to 24 000 Hz). The KRYPTON 9 is also equipped with two 17 cm diameter bass drivers. Their cone in cellulose pulp treated and hardened allows to obtain a deep and dynamic bass. The unique treatment of the membranes is realized in our workshop in France, according to a strict schedule of conditions. It brings a rigidity which will strongly decrease the deformation and consequently will make the bass firmer, more realistic. All its drivers are surrounded by a circular foam which reduces the problems of rebounds of waves near the emissive sources. The aim of course is to make the message more detailed, more precise.

Regarding the design...

Available in 3 very trendy finishes, the KRYPTON 9 is proposed with a magnetic cover, itself covered with a mottled fabric of the most beautiful effect. A base is screwed on the bottom of the speaker to slightly incline the top of the speaker towards the back and thus allow a perfect phasing of the drivers. Note also that small anti-slip pads act as decoupling of the speaker from its support. Spikes are also provided.

A speaker easy to live with...

Beautiful, slender, with a laminar decompression port on the front, the Krypton 9 is a speaker easy to power. Its neutral character and its good performance will allow it to be coupled with all the current electronics of the market.



3 different finishes :



Bass reflex : laminar port
Nom. Power : 150 W
Max. Power : 200 W
Number of ways : 3
Number of speakers : 4
Sensitivity : 93 dB

Frequency range : 35-24000 Hz
Tweeter : 28mm soft dome
Midrange : Kevlar 13 cm (5 inch)
Woofer : 2 x 17 cm (6,7 inch) cellulose
Impedance : 4...8 ohms
Frequencies cut : 400/4000 Hz