

Sonus faber
Chameleon
collection

The freedom to select
the most suitable "dress" for your speakers.





Sonus faber *Chameleon T.* ITALY
Sonus faber *Chameleon B.* ITALY
Sonus faber *Chameleon C.* ITALY



DATA SHEET

SYSTEM
2 way bookshelf vented box

LOUDSPEAKERS
Tw: Ø 29 mm
Md: Ø 150 mm
W: 2 x Ø 180 mm

CROSS-OVER
250Hz - 2.500Hz

FREQUENCY RESPONSE
38 Hz - 25.000 Hz

SENSITIVITY
90 dB SPL (2.83V/1m)

NOMINAL IMPEDANCE
4 ohm

**SUGGESTED AMPLIFIER
POWER OUTPUT**
40W - 300W without clipping

LONG-TERM MAX INPUT VOLTAGE
(IEC 268-5)
22 V rms

DIMENSIONS (HxWxD)
1060 x 270 x 355 mm
41,7 x 10,6 x 14 in

WEIGHT
24,5 Kg ea - net weight
54 lb ea - net weight

SYSTEM
2 way bookshelf vented box

LOUDSPEAKERS
Tw: Ø 29 mm
Md: Ø 150 mm

CROSS-OVER
2.500Hz

FREQUENCY RESPONSE
87 dB SPL (2.83V/1m)

SENSITIVITY
87 dB SPL (2.83V/1m)

NOMINAL IMPEDANCE
4 ohm

**SUGGESTED AMPLIFIER
POWER OUTPUT**
30W - 150W without clipping

LONG-TERM MAX INPUT VOLTAGE
(IEC 268-5)
20V rms

DIMENSIONS (HxWxD)
315,5 x 185 x 283 mm
12,4 x 7,3 x 11 in
724 x 306 x 370 mm (optional dedicated stand)
28,5 x 12 x 14,5 in (optional dedicated stand)

WEIGHT
6,7 Kg ea - net weight
14,8 lb ea - net weight
12,7 Kg ea - dedicated stand incl. (optional)
27,9 lb ea - dedicated stand incl. (optional)

SYSTEM
2 way closed box with passive radiator

LOUDSPEAKERS
Tw: Ø 29 mm
Md: Ø 150 mm
Pr: Ø 150 mm

CROSS-OVER
2.000Hz

FREQUENCY RESPONSE
50 Hz - 25.000 Hz

SENSITIVITY
87 dB SPL (2.83V/1m)

NOMINAL IMPEDANCE
4 ohm

**SUGGESTED AMPLIFIER
POWER OUTPUT**
50W - 300W, without clipping

LONG-TERM MAX INPUT VOLTAGE
(IEC 268-5)
22 V rms

DIMENSIONS (HxWxD)
199 x 540 x 228 mm
7,8 x 21,2 x 9 in

WEIGHT
8,1 Kg ea - net weight
17,8 lb ea - net weight

FINISHES

WALNUT MATTE



METAL BLUE



METAL GREY



RED GLOSS



ORANGE GLOSS



WHITE GLOSS



PIANO BLACK

