

ATS5

Profile Dolby Atmos Enabled In-Wall Speaker System FIVE

Profile ATS FIVE Dolby Atmos Enabled Speaker System includes the following; ATX100 Dolby Atmos Enabled In-Wall Height Speaker + Profile AIM LCR5 FIVE In-Wall LCR Speaker + GRLATXPROAIM Dolby Atmos Enabled System Grille Kit

ATS3

Profile Dolby Atmos Enabled In-Wall Speaker System THREE

Profile ATS THREE Dolby Atmos Enabled Speaker System includes the following; ATX100 Dolby Atmos Enabled In-Wall Height Speaker + Profile AIM LCR5 THREE In-Wall LCR Speaker + GRLATXPROAIM Dolby Atmos Enabled System Grille Kit

ATS1

Profile Dolby Atmos Enabled In-Wall Speaker System ONE

Profile ATS ONE Dolby Atmos Enabled Speaker System includes the following; ATX100 Dolby Atmos Enabled In-Wall Height Speaker + Profile AIM LCR5 ONE In-Wall LCR Speaker + GRLATXPROAIM Dolby Atmos Enabled System Grille Kit

ATS500

AIM Series 2 Dolby Atmos Enabled In-Wall Speaker System 500

AIM ATS 500 Series 2 Dolby Atmos Enabled Speaker System includes the following; ATX100 Dolby Atmos Enabled In-Wall Height Speaker + AIM LCR5 FIVE Series 2 In-Wall LCR Speaker + GRLATXAIM2 AIM Series 2 Dolby Atmos Enabled System Grille Kit

ATS200

AIM Series 2 Dolby Atmos Enabled In-Wall Speaker System 200

AIM ATS 200 Series 2 Dolby Atmos Enabled Speaker System includes the following; ATX100 Dolby Atmos Enabled In-Wall Height Speaker + AIM LCR5 TWO Series 2 In-Wall LCR Speaker + GRLATXAIM2 AIM Series 2 Dolby Atmos Enabled System Grille Kit



Profile AIM8 FIVE

In-Ceiling Aim-able Speaker

Order# ASM58501-2

- Flangeless Appearance
- Power Handling: 150 Watts
- Pivoting 8" Kevlar® Woofer
- Adjustable Impedance: 8/6/4 Ohm
- Pivoting 1" Aluminum/Magnesium Tweeter
- Frequency Response: 33Hz - 20kHz
- WavePlane Technology
- Diameter x Depth: 11" x 5 3/4" 279mm x 146mm (with Grille)
- Bass and Treble EQ Switches
- Cut-Out Diameter: 9 3/4" (248mm)
- Accu-Grille Technology
- Timbre-Matched to All FIVE Series
- Sensitivity: 91dB 1W/1m



Profile AIM8 THREE

In-Ceiling Aim-able Speaker

Order# ASM58301-2

- Flangeless Appearance
- Power Handling: 150 Watts
- Pivoting 8" Aluminum Woofer
- Adjustable Impedance: 8/6/4 Ohm
- Pivoting 1" Aluminum Tweeter
- Frequency Response: 37Hz - 20kHz
- WavePlane Technology
- Diameter x Depth: 11" x 5 3/4" 279mm x 146mm (with Grille)
- Bass and Treble EQ Switches
- Cut-Out Diameter: 9 3/4" (248mm)
- Accu-Grille Technology
- Timbre-Matched to All THREE Series
- Sensitivity: 89dB 1W/1m



Profile AIM8 TWO

In-Ceiling Aim-able
Speaker

Order# ASM58201-2

- Flangeless Appearance
- Pivoting 8" Resin Reinforced Fiberglass Woofer
- Pivoting 1" Treated Silk Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Accu-Grille Technology
- Timbre-Matched to All TWO Series
- Sensitivity: 89dB 1W/1m
- Power Handling: 125 Watts
- Impedance: 8 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 11" x 5 3/4" 279mm x 146mm (with Grille)
- Cut-Out Diameter: 9 3/4" (248mm)



Profile AIM8 ONE

In-Ceiling Aim-able
Speaker

Order# ASM58101-2

- Flangeless Appearance
- Pivoting 8" Polypropylene Woofer
- Pivoting 1" Treated Silk Tweeter
- WavePlane Technology
- Timbre-Matched to All ONE Series
- Sensitivity: 88dB 1W/1m
- Power Handling: 125 Watts
- Impedance: 8 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 11" x 5 3/4" 279mm x 146mm (with Grille)
- Cut-Out Diameter: 9 3/4" (248mm)



Profile AIM7 FIVE

In-Ceiling Aim-able
Speaker

Order# ASM57501-2

- Flangeless Appearance
- Pivoting 7" Kevlar® Woofer
- Pivoting 1" Aluminum/ Magnesium Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 91dB 1W/1m
- Power Handling: 150 Watts
- Adjustable Impedance: 8/6/4 Ohm
- Frequency Response: 35Hz - 20kHz
- Diameter x Depth: 9 5/8" x 5 1/8" 244mm x 130mm (with Grille)
- Cut-Out Diameter: 8 1/4" (210mm)



Profile AIM7 THREE

In-Ceiling Aim-able
Speaker

Order# ASM57301-2

- Flangeless Appearance
- Pivoting 7" Aluminum Woofer
- Pivoting 1" Aluminum Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 91dB 1W/1m
- Power Handling: 125 Watts
- Adjustable Impedance: 8/6/4 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 9 5/8" x 5 1/8" 244mm x 130mm (with Grille)
- Cut-Out Diameter: 8 1/4" (210mm)



Profile AIM7 TWO

In-Ceiling Aim-able
Speaker

Order# ASM57201-2

- Flangeless Appearance
- Pivoting 7" Resin Reinforced Fiberglass Woofer
- Pivoting 1" Silk Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 90dB 1W/1m
- Power Handling: 125 Watts
- Impedance: 8 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 9 5/8" x 5 1/8" 244mm x 130mm (with Grille)
- Cut-Out Diameter: 8 1/4" (210mm)



Profile AIM5 THREE

In-Ceiling Aim-able
Speaker

Order# ASM55301-2

- Flangeless Appearance
- Pivoting 5 1/4" Aluminum Woofer
- Pivoting 3/4" Aluminum Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 89dB 1W/1m
- Power Handling: 100 Watts
- Adjustable Impedance: 8/6/4 Ohm
- Frequency Response: 50Hz - 20kHz
- Diameter x Depth: 8" x 4 1/2" 203mm x 114mm (with Grille)
- Cut-Out Diameter: 6 5/8" (168mm)



Profile AIM5 ONE

In-Ceiling Aim-able
Speaker

Order# ASM55101-2

- Flangeless Appearance
- Pivoting 5 1/4" Polypropylene Woofer
- Pivoting 3/4" Treated Silk Tweeter
- WavePlane Technology
- Timbre-Matched to All ONE Series
- Sensitivity: 88dB 1W/1m
- Power Handling: 75 Watts
- Impedance: 8 Ohm
- Frequency Response: 55Hz - 20kHz
- Diameter x Depth: 8" x 4 1/2" 203mm x 114mm (with Grille)
- Cut-Out Diameter: 6 5/8" (168mm)



Profile AIM8 DT THREE

Dual-Tweeter Aimable Speakers

Order# ASM58603-2

- Flangeless Appearance
- Pivoting 8" Aluminum Dual Voice Coil Woofer and Rubber Surround
- Dual Pivoting 1" Aluminum Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Timbre Matched to All THREE Series
- Sensitivity: 92dB 1W/1m
- Power Handling: 100 Watts
- Impedance: 8 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 10 3/4" x 5 1/2" 273mm x 140mm (with Grille)
- Cut-Out Diameter: 9 3/4" (248mm)



Profile AIM7 DT THREE

Dual-Tweeter Aimable Speakers

Order# ASM57603-2

- Flangeless Appearance
- Pivoting 7" Aluminum Dual Voice Coil Woofer and Rubber Surround
- Dual Pivoting 1" Aluminum Tweeters
- WavePlane Technology
- Bass and Treble EQ Switches
- Timbre Matched to All THREE Series
- Sensitivity: 92dB 1W/1m
- Power Handling: 60 Watts
- Impedance: 8 Ohm
- Frequency Response: 50Hz - 20kHz
- Diameter x Depth: 9 5/8" x 4 3/4" 244mm x 121mm (with Grille)
- Cut-Out Diameter: 8 1/4" (210mm)



Profile AIM8 WIDE THREE

Wide Dispersion Speaker

Order# ASM50831-2

- 3-Way Fully-Pivoting In-Ceiling Speaker featuring an 8" Woofer, Dual 2" Midranges and Dual 3/4" Tweeters
- Flangeless Appearance with Magnetically Attached Full Coverage Steel Grille
- Pivoting 8" Aluminum Cone Woofer
- Dual 2" Aluminum Inverted Dome Midrange Drivers
- Dual 3/4" Aluminum Dome Tweeters
- Ambient/Wide & Treble Switches
- Timbre-Matched to All THREE Series Speakers
- Sensitivity: 91dB 1W/1m
- Power Handling: 150 Watts
- Impedance: 8 Ohm
- Frequency Response: 37Hz - 20kHz
- Diameter x Depth: 11 7/16" x 6 1/2" (291mm x 165mm)
- Cut-Out Diameter: 9 3/4" (248mm)



Profile AIM8 WIDE ONE

Wide Dispersion Speaker

Order# ASM50811-2

- 3-Way Fully-Pivoting In-Ceiling Speaker featuring an 8" Woofer, Dual 2" Midranges and Dual 3/4" Tweeters
- Flangeless Appearance with Magnetically Attached Full Coverage Steel Grille
- Pivoting 8" Graphite Cone Woofer
- Dual 2" Graphite Inverted Dome Midrange Drivers
- Dual 3/4" Silk Dome Tweeters
- Front-Mounted Ambient/Wide Switch
- Timbre-Matched to All ONE Series Speakers
- Sensitivity: 88dB 1W/1m
- Power Handling: 125 Watts
- Impedance: 8 Ohm Compatible
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 11 7/16" x 6 1/2" (291mm x 165mm)
- Cut-Out Diameter: 9 3/4" (248mm)



Profile AIM Cinema FIVE

Aim-able Speaker
Order# ASM59105-2

- Flangeless Appearance
- Pivoting 1" Aluminum/Magnesium Tweeter
- Two 5 1/4" Kevlar® Woofers with Phase Plugs
- Two 6" Kevlar® Impregnated Paper Woofers
- Treble, Mid & Bass EQ Switches
- Bi-Amping Feature
- Timbre-Matched to All FIVE Series
- Sensitivity: 91dB 1W/1m
- Power Handling: 200 Watts
- Impedance: 8 Ohm Compatible
- Frequency Response: 35Hz - 20kHz
- Dimensions: (H x W x D) 30 1/4" x 9" x 4" 768mm x 229mm x 102mm (with Grille)
- Wall Cut-Out: (H x W) 28 3/4" x 7 1/2" 730mm x 191mm



Profile AIM Cinema THREE

Aim-able Speaker
Order# ASM59103-2

- Flangeless Appearance
- Pivoting 1" Aluminum Tweeter
- Two 5 1/4" Aluminum Woofers with Phase Plugs
- Two 6" Kevlar® Impregnated Paper Woofers
- Treble, Mid & Bass EQ Switches
- Bi-Amping Feature
- Timbre-Matched to All THREE Series
- Sensitivity: 90dB 1W/1m
- Power Handling: 175 Watts
- Impedance: 8 Ohm Compatible
- Frequency Response: 39Hz - 20kHz
- Dimensions: (H x W x D) 30 1/4" x 9" x 4" 768mm x 229mm x 102mm (with Grille)
- Wall Cut-Out: (H x W) 28 3/4" x 7 1/2" 730mm x 191mm



Profile AIM Cinema ONE

Aim-able Speaker
Order# ASM59101-2

- Flangeless Appearance
- Pivoting 1" Silk Tweeter
- Two 5 1/4" Graphite Woofers with Phase Plugs
- Two 6" Kevlar® Impregnated Paper Woofers
- Bass EQ Switch
- Bi-Amping Feature
- Timbre-Matched to All ONE Series
- Sensitivity: 89dB 1W/1m
- Power Handling: 125 Watts
- Impedance: 8 Ohm Compatible
- Frequency Response: 40Hz - 20kHz
- Dimensions: (H x W x D) 30 1/4" x 9" x 4" 768mm x 229mm x 102mm (with Grille)
- Wall Cut-Out: (H x W) 28 3/4" x 7 1/2" 730mm x 191mm





Profile AIM LCR5 FIVE

Aim-able Speaker
Order# ASM54655-2

- 2-Way In-Wall LCR (Left, Center, Right) Speaker with Dual 5 1/4" Woofers and 1" Tweeter mounted on a Pivoting Speaker Baffle
- Flangeless Appearance with Magnetically Attached Full Coverage Steel Grille
- Pivoting Speaker Baffle
- Two - 5 1/4" Kevlar® Woofers with Phase Plugs
- Independently Pivoting 1" Aluminum/Magnesium Dome Tweeter
- Bass & Treble EQ Switches
- Timbre-Matched to All FIVE Series Speakers
- Sensitivity: 91dB 1W/1m
- Power Handling: 100 Watts
- Adjustable Impedance: 8/6 Ohm
- Frequency Response: 48Hz - 20kHz
- Dimensions: (H x W x D) 17 7/16" x 9 1/4" x 4" 235mm x 443mm x 102mm
- Wall Cut-Out: (H x W) 14 1/4" x 7 1/2" (362mm x 190mm)



Profile AIM LCR5 THREE

Aim-able Speaker
Order# ASM54633-2

- Flangeless Appearance
- Pivoting Baffle
- Two 5 1/4" Aluminum/Magnesium Woofers with Phase Plugs
- Pivoting 1" Aluminum/Magnesium Tweeter
- Bass & Treble EQ Switches
- Timbre-Matched to All THREE/FOUR Series speakers
- Sensitivity: 90dB 1W/1m
- Power Handling: 100 Watts
- Adjustable Impedance: 8/6 Ohm
- Frequency Response: 50Hz - 20kHz
- Dimensions: (H x W x D) 17 1/8" x 9" x 4" 443mm x 235mm x 102mm (with Grille)
- Wall Cut-Out: (H x W) 14 1/4" x 7 1/2" 362mm x 190mm



Profile AIM LCR5 ONE

Aim-able Speaker
Order# ASM54611-2

- Flangeless Appearance
- Pivoting Baffle
- Two 5 1/4" Graphite Woofers with Phase Plugs
- Pivoting 1" Silk Dome Tweeter
- Timbre-Matched to All ONE Series
- Sensitivity: 89dB 1W/1m
- Power Handling: 80 Watts
- Impedance: 8 Ohm
- Frequency Response: 55Hz - 20kHz
- Dimensions: (H x W x D) 17 1/8" x 9" x 4" 235mm x 443mm x 102mm (with Grille)
- Wall Cut-Out: (H x W) 7 1/2" x 14 1/4" 190mm x 362mm



Profile AIM LCR3 FIVE

Aim-able Speaker
Order# ASM54651-2

- 2-Way In-Wall LCR (Left, Center, Right) Speaker with Dual 3" Woofers and 3/4" Tweeter mounted on a Pivoting Speaker Baffle
- Flangeless Appearance with Magnetically Attached Full Coverage Steel Grille
- Pivoting Speaker Baffle
- Independently Pivoting 3/4" Aluminum/Magnesium Dome Tweeter
- 2-Position Treble EQ Switch
- Timbre-Matched to All FIVE Series Speakers
- Sensitivity: 86dB 1W/1m
- Power Handling: 60 Watts
- Impedance: 8 Ohm Compatible
- Frequency Response: 60Hz - 20kHz
- Dimensions: (H x W x D) 10" x 5 3/4" x 3" 254mm x 146mm x 76mm
- Wall Cut-Out: (H x W) 9" x 4 3/4" 227mm x 120mm



Profile AIM LCR3 THREE

Aim-able Speaker
Order# ASM54631-2

- Flangeless Appearance
- Pivoting Baffle
- Two 3" Aluminum Woofers with Phase Plugs
- Pivoting 3/4" Aluminum Tweeter
- 2-Position Treble EQ Switch
- Sensitivity: 86dB 1W/1m
- Power Handling: 60 Watts
- Impedance: 8 Ohm
- Frequency Response: 78Hz - 20kHz
- Dimensions: (H x W x D) 10 1/2" x 6" x 3" 254mm x 146mm x 76mm (with Grille)
- Wall Cut-Out: (H x W) 9" x 4 3/4" 227mm x 120mm



Profile AIM LCR3 ONE

Aim-able Speaker
Order# ASM54311-2

- Flangeless Appearance
- Pivoting Baffle
- Two 3" Graphite Woofers with Phase Plugs
- Pivoting 3/4" Silk Tweeter
- Timbre-Matched to All ONE Series
- Sensitivity: 85dB 1W/1m
- Power Handling: 60 Watts
- Impedance: 8 Ohm
- Frequency Response: 80Hz - 20kHz
- Dimensions: (H x W x D) 10 1/2" x 6" x 3" 254mm x 146mm x 76mm (with Grille)
- Wall Cut-Out: (H x W) 9" x 4 3/4" 227mm x 120mm



Profile AIM7 MT THREE

Aim-able Speaker

Order# **ASM57703-2**

- Flangeless Appearance
- 7" Aluminum Woofer with Phase Plug
- Pivoting 1" Aluminum Tweeter
- Bass & Treble EQ Switches
- Timbre-Matched to All THREE Series
- Sensitivity: 91dB 1W/1m
- Power Handling: 125 Watts
- Impedance: 8/6 Ohm
- Frequency Response: 40Hz - 20kHz
- Dimensions: (H x W x D) (Full Pivot) 14" x 9 1/2" x 4" 356mm x 241mm x 102mm (with Grille)
- Wall Cut-Out Dimensions: (H x W) 12 3/4" x 8 1/16" 324mm x 206mm



Profile Cinema Sub 10

Subwoofer

Order# **ASM59010-2**

- Flangeless Appearance
- 10" Reinforced Treated Paper Cone Woofer with Dual Voice Coil
- Enhanced Performance and Look
- Sensitivity: 89dB 1W/1m
- Power Handling: 250 Watts
- Impedance: 4 Ohms per Coil
- Frequency Response: 30Hz - 800Hz
- Dimensions: (H x W x D) 13 5/8" x 13 5/8" x 3 7/8" 346mm x 346mm x 98mm
- Cut-Out Dimensions: (H x W) 12 1/8" x 12 1/8" 308mm x 308mm





Profile CRS8 THREE

Custom Round Series
Order# **ASM56803-2**

- Flangeless Appearance
- 8" Aluminum Woofer
- Pivoting 1" Aluminum Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 90dB 1W/1m
- Power Handling: 125 Watts

- Adjustable Impedance: 8/6/4 Ohm
- Frequency Response: 38Hz - 20kHz
- Diameter x Depth: 11 1/8" x 4 1/2" 303mm x 114mm (with Grille)
- Cut-Out Diameter: 9 3/4" (248mm)



Profile CRS8 TWO

Custom Round Series
Order# **ASM56802-2**

- Flangeless Appearance
- 8" Glass Composite Woofer
- Pivoting 1" Silk Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 90dB 1W/1m
- Power Handling: 100Watts
- Adjustable Impedance: 8/6/4 Ohm

- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 11 1/8" x 4 1/2" 303mm x 114mm (with Grille)
- Cut-Out Diameter: 9 3/4" (248mm)



Profile CRS8 ONE

Custom Round Series
Order# **ASM56801-2**

- Flangeless Appearance
- 8" Polypropylene Woofer
- Pivoting 1" Silk Tweeter
- WavePlane Technology
- Timbre-Matched to All ONE Series
- Sensitivity: 89dB 1W/1m
- Power Handling: 100 Watts
- Impedance: 8 Ohm

- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 11 1/8" x 4 1/2" 303mm x 114mm (with Grille)
- Cut-Out Diameter: 9 3/4" (248mm)





Profile CRS6 THREE

Custom Round Series
Order# ASM56603-2

- Flangeless Appearance
- 6 1/2" Aluminum Woofer
- Pivoting 1" Aluminum Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 90dB 1W/1m
- Power Handling: 125 Watts

- Adjustable Impedance: 8/6/4 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 9 5/8" x 4 1/16" 249mm x 103mm (with Grille)
- Cut-Out Diameter: 8 1/4" (210mm)



Profile CRS6 TWO

Custom Round Series
Order# ASM56602-2

- Flangeless Appearance
- 6 1/2" Glass Composite Woofer
- Pivoting 1" Silk Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 92dB 1W/1m
- Power Handling: 120 Watts
- Impedance: 8 Ohm

- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 9 5/8" x 4 1/16" 249mm x 103mm (with Grille)
- Cut-Out Diameter: 8 1/4" (210mm)



Profile CRS6 ONE

Custom Round Series
Order# ASM56601-2

- Flangeless Appearance
- 6 1/2" Polypropylene Woofer
- Pivoting 1" Silk Tweeter
- WavePlane Technology
- Timbre-Matched to All ONE Series
- Sensitivity: 92dB 1W/1m
- Power Handling: 100 Watts

- Impedance: 8 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 9 5/8" x 4 1/16" 249mm x 103mm (with Grille)
- Cut-Out Diameter: 8 1/4" (210mm)



Profile CRS5.2

Custom Round Series

Order# **ASM52000-2**

- Flangeless Appearance
- 5 1/4" Polypropylene Woofer
- 1/2" Liquid Cooled Polyamide Tweeter
- Sensitivity: 91dB 1W/1m
- Power Handling: 50 Watts
- Impedance: 8 Ohm
- Frequency Response: 55Hz - 20kHz
- Diameter x Depth: 8" x 3 1/4" 203mm x 83mm (with Grille)
- Cut-Out Diameter: 6 3/4" (171mm)



Profile CRS3

Custom Round Series

Order# **ASM56301-2**

- Flangeless Appearance
- 3" Aluminum Woofer
- Timbre-Matched to All THREE Series
- Sensitivity: 86dB 1W/1m
- Power Handling: 40 Watts
- Impedance: 8 Ohm
- Frequency Response: 80Hz - 16kHz
- Diameter x Depth: 5 3/8" x 3 1/4" 137mm x 83mm (with Grille)
- Cut-Out Diameter: 4 1/2" (113mm)





Profile AccuFit CRS7 THREE

Contained Sound
Custom Round Series

Order# ASM56703-2

- Flangeless Appearance
- 7" Aluminum Woofer
- 3/4" Pivoting Aluminum Tweeter
- Treble Equalization Switch
- Sealed Steel Enclosure
- WavePlane Technology
- Sensitivity: 92dB 1W/1m
- Power Handling: 125 Watts
- Impedance: 8 Ohm
- Frequency Response: 50Hz - 20kHz
- STL (Sound Transmission Loss) Feature
- Diameter x Depth: 9 5/8" x 2 7/8" 244mm x 70mm (with Grille)
- Cut-Out Diameter: 8 1/4" (210mm)

Installation Note: AccuFit Speakers

The finest flush-mount speakers in the world are useless if they cannot be installed due to restrictions in a specific building's walls or ceiling. It may be a matter of sound penetrating an adjoining wall, unique code restrictions, or simply the customer's requirements. SpeakerCraft offers the AccuFit Series to address space limitations, building codes, and living environment concerns.

The AccuFit series of shallow-depth, fully enclosed architectural speakers have the proper amount of air space to deliver the best sound performance regardless of the installation environment. This line of technically advanced speakers will fit just about any installation.



Profile AccuFit Ultra Slim ONE

Shallow Depth
In-Ceiling Speaker

Order# ASM53101-2

- 3-Way, Shallow-Depth, Tuned Port, Magnetically Shielded Steel Enclosure
- Flangeless Appearance with Magnetically Attached Full Coverage Steel Grille
- Two 3" Custom Polypropylene Inverted Dome Woofers
- Two 3" Custom Aluminum Inverted Dome Midrange Drivers
- 3/4" Resin Coated Silk Dome Tweeter
- Extreme Shallow-Depth Mounting Capability, Needing only 2" (51mm) of Depth
- Timbre-Matched to All ONE Series Speakers
- Sensitivity: 89dB 1W/1m
- Power Handling: 60 Watts
- Impedance: 8 Ohm
- Frequency Response: 90Hz - 20kHz
- STL (Sound Transmission Loss) Feature, 20dBA Sound Reduction / Measuring signal: Pink Noise
- Diameter x Depth: 9 15/16" x 2" 252mm x 51mm
- Cut-Out Diameter: 8 1/4" (210mm)



Profile AccuFit Ultra Slim THREE

Shallow Depth
In-Ceiling Speaker

Order# ASM53301-2

- 3-Way, Shallow-Depth, Tuned Port, Magnetically Shielded Steel Enclosure
- Flangeless Appearance with Magnetically Attached Full Coverage Steel Grille
- Two 3" Custom Aluminum Inverted Dome Woofers
- Two 3" Custom Aluminum Inverted Dome Midrange Drivers
- 3/4" Aluminum Tweeter
- Extreme Shallow-Depth Mounting Capability, Needing only 2" (51mm) of Depth
- Timbre-Matched to All THREE Series Speakers
- Sensitivity: 90dB 1W/1m
- Power Handling: 60 Watts
- Impedance: 8 Ohm
- Frequency Response: 90Hz - 20kHz
- STL (Sound Transmission Loss) Feature, 20dBA Sound Reduction / Measuring signal: Pink Noise
- Diameter x Depth: 9 15/16" x 2" 252mm x 51mm
- Cut-Out Diameter: 8 1/4" (210mm)