

LEO1 Details matter.

Design.

Dimensions

Speaker: 700 (W) x 271 (H) x 99 (D) Speaker with table top stand: 700 (W) x 323 (H) x 159 (D)

Materials

Aluminium speaker trim Laser cut aluminium rear grille Ultrasonic welded acoustic cloth speaker grille cover Stainless steel custom supporting feet

Finish

Black, White

Sound.

Operating modes

Single LE01 unit – Integrated stereo speaker (landscape orientation), Mono (portrait orientation)

2 x LE01 units stereo paired – Left/right channel stereo

Audio technology

2 x custom designed 5.25" aluminium cone high-excursion fasttransient woofers with NdFe motors 3 x full-range 2.5" Balanced Mode Radiator drive units

2 x race track/quadratic 8" x 4.5" customised passive radiators 3 x monolithic HD class-D power amplifiers 32-bit ARM core digital signal processor for high accuracy and low noise Frequency response: 62 Hz - 21500 Hz (-6dB)

96kHz/24-bit HD audio streaming Supported audio formats: HE-AAC, LC-AAC, MP3, Vorbis, WAV (LPCM), FLAC, Opus

Audio inputs

Apple Airplay 2 Chromecast™ built-in Bluetooth® 4.2 with AAC 3.5mm Aux-in

Features.

Room placement audio EQ optimisation Auto source switching (Wi-Fi, Bluetooth, Aux) Multiroom & stereo pairing: Airplay 2, Chromecast Bass & treble tone control (in App) Dual-positioned 4-microphone beamforming arrays for far-field voice recognition and acoustic echo-cancellation Physical privacy button to disconnect the microphones

Controls

Voice: the Google Assistant Physical controls: privacy button, action button, play/pause, track skip forward, track skip back, volume +, volume –, Bluetooth pairing

Networking

Wi-Fi dual band (WLAN 802.11a/b/g/n/ac, 2.4 and 5 GHz) 10/100 Mbps Ethernet port

What's in the box.

LE01 speaker 1.5m AC power adaptor Stainless steel natural finish table top stand Silicone feet Quick start guide Safety sheet

Accessories. (sold separately)

Floor stand Wall bracket

Good to know.

Compatibility

An iPhone or iPad with iOS 10.3 and higher An Android™ phone running Android 5.0 and higher An Android tablet running Android 6.0 and higher

Warranty

2-year warranty

Electrical & environmental performance

Operational temperature range: 0 C to 40 C Storage temperature range: 0 C to 40 C Operational humidity range: 10% to Max 90% (No condensation) Storage humidity range: 10% to Max 90% (No condensation) UV Degradation: No degradation due to UV for 3 years Line voltage: 100V to 240V AC Frequency: 50Hz to 60Hz



braun-audio.com

E&OE.

Braun Audio reserves the right to amend details of the specifications without notice in line with technical developments. Certain trademarks used under license from The Procter & Gamble company or its affiliates.



LE02 **Details matter.**

Design.

Dimensions

Speaker: 480 (W) x 171 (H) x 84.5 (D) Speaker with table-top stand: 480 (W) x 210 (H) x 131.5 (D)

Materials

Aluminium speaker trim Laser cut aluminium rear grille Ultrasonic welded acoustic cloth speaker grille cover Stainless steel custom supporting feet

Finish

Black, White

Sound.

Operating modes

Single LEO2 unit – Integrated stereo speaker (landscape orientation), Mono (portrait orientation)

2 x LE02 units stereo paired – Left/right channel stereo

Audio technology

1 x custom designed 5.5" aluminium cone high-excursion fast-transient woofers with NdFe motors

2 x full-range 2.25" Balanced Mode Radiator drive units

2 x race track/quadratic 6" x 3.5" customised passive radiators

2 x Monolithic HD class-D power amplifiers

32-bit ARM-core digital signal processor for high accuracy and low noise $% \left({{{\rm{ARM}}} \right)$

Frequency response: 67 Hz - 20500 Hz (-6dB) 96kHz/24-bit HD audio streaming Supported audio formats: HE-AAC, LC-AAC, MP3, Vorbis, WAV (LPCM), FLAC, Opus

Audio inputs

Apple Airplay 2 Chromecast™ built-in Bluetooth® 4.2 with AAC 3.5mm Aux-in

Features.

Room placement audio EQ optimisation Auto source switching (Wi-Fi, Bluetooth, Aux) Multiroom & stereo pairing: Airplay 2, Chromecast Bass & treble tone control (in App) Dual-positioned 4-microphone beamforming arrays for far-field voice recognition and acoustic echo-cancellation Physical privacy button to disconnect the microphones

Controls

Voice: the Google Assistant Physical controls: privacy button, action button, play/pause, track skip forward, track skip back, volume +, volume –, Bluetooth pairing

Networking

Wi-Fi dual-band (WLAN 802.11a/b/g/n/ac, 2.4 and 5 GHz) 10/100 Mbps Ethernet port 10/100 Mbps Ethernet port

What's in the box.

LE02 speaker 1.5m AC power adaptor Stainless steel natural finish table top stand Silicone feet Quick start guide Safety sheet

Accessories. (sold separately)

Floor stand Wall bracket

Good to know.

Compatibility

An iPhone or iPad with iOS 10.3 and higher An Android™ phone running Android 5.0 and higher An Android tablet running Android 6.0 and higher

Warranty

2-year warranty

Electrical & environmental performance

Operational temperature range: 0 C to 40 C Storage temperature range: 0 C to 40 C Operational humidity range: 10% to Max 90% (No condensation) Storage humidity range: 10% to Max 90% (No condensation) UV Degradation: No degradation due to UV for 3 years Line voltage: 100V to 240V AC Frequency: 50Hz to 60Hz



braun-audio.com

E&OE.

Braun Audio reserves the right to amend details of the specifications without notice in line with technical developments. Certain trademarks used under license from The Procter & Gamble company or its affiliates.

BRAUN



LE03 **Details matter.**

Design.

Dimensions 170 (W) x 170 (H) x 84 (D)

Materials Aluminium speaker trim Ultrasonic welded acoustic cloth speaker grille cover

Finish Black, White

Sound.

Operating modes Single LE03 unit – Mono 2 x LE03 units stereo paired – Left/right channel stereo

Audio technology

1 x Custom-designed 3.5" aluminium cone high-excursion fast-transient woofer with NdFe motor
1 x Full-range 1.5" Balanced Mode Radiator drive unit
1 x Race track/quadratic 5" x 3" Customised passive radiator
1 x Monolithic class-D power amplifier
Frequency response: 70 Hz - 21000 Hz (-6dB)
32-bit ARM-core digital signal processor for high accuracy & low noise
96kHz/24-bit HD audio streaming
Supported audio formats:
HE-AAC, LC-AAC, MP3, Vorbis, WAV (LPCM), FLAC, Opus

Audio inputs

Apple Airplay 2 Chromecast[™] built-in Bluetooth[®] 4.2 with AAC 3.5mm Aux-in

Features.

Room placement audio EQ optimisation Auto source switching (Wi-Fi, Bluetooth, Aux) Multi-room & stereo pairing: Airplay 2, Chromecast Bass & treble tone control (in App) 2-microphone beamforming array for far-field voice recognition and acoustic echo-cancellation Physical privacy button to disconnect the microphones

What's in the box.

LE03 speaker 1.5m AC power adaptor Silicone feet Quick start guide Safety sheet

Accessories. (sold separately)

Floor stand Wall bracket

Good to know.

Compatibility

An iPhone or iPad with iOS 10.3 and higher An Android™ phone running Android 5.0 and higher An Android tablet running Android 6.0 and higher

Warranty

2-year warranty **Electrical & environmental performance** Operational temperature range: 0 C to 40 C Storage temperature range: 0 C to 40 C

Operational humidity range: 10% to Max 90% (No condensation) Storage humidity range: 10% to Max 90% (No condensation) UV Degradation: No degradation due to UV for 3 years Line voltage: 100V to 240V AC Frequency: 50Hz to 60Hz



braun-audio.com

E&OE.

Braun Audio reserves the right to amend details of the specifications without notice in line with technical developments. Certain trademarks used under license from The Procter & Gamble company or its affiliates.