

A-LINE



SPENDOR

MADE FOR MUSIC. DESIGNED FOR YOU.

Our new Spondor A-Line loudspeakers prove you don't need a big space, or budget, to enjoy dynamic, open and exhilarating sound. If you're someone who truly loves music, whichever model you chose, they will add a whole new dimension to your listening pleasure.

They are slim, compact and you can place them easily and unobtrusively into your living space and they will fill the room with a clear captivating sound. And thanks to innovative Spondor technology the A-Line loudspeakers will get the very best from whatever equipment you have.

**WHAT HI-FI?
AWARDS 2017**

Stereo speakers
Best floorstander £2000+
Spondor A4

Looking for a good pair of compact premium floorstanders? Spondor's new A4s could be exactly what you're after. They're beautifully engineered, smartly finished and sound great.

WHAT HI-FI AWARDS 2017

The new Spondor A-Line loudspeakers deliver class leading performance. They are the most adaptable and affordable loudspeakers we have ever created.

HIGHLIGHTS

- Engineering innovation from the multi-award winning Spondor SA1, A6R and D7 loudspeakers
- New Spondor EP77 Polymer cones
- Three elegant natural veneer finishes with premium options
- Deep articulate bass
- Calibrated and matched to broadcast reference standard
- British design and manufacture
- Grilles available as a cost option

TECHNICAL SPECIFICATION

MODEL	DESCRIPTION	DRIVE UNITS	H x W x D	WEIGHT
A1	2-way shelf mount	LF 150mm, HF 22mm	308 x 165 x 186mm	5kg
A2	2-way floorstanding	LF 150mm, HF 22mm	786 x 150 x 258mm	12kg
A4	2-way floorstanding	LF 180mm, HF 22mm	861 x 165 x 284mm	16kg
A7	2-way floorstanding	LF 180mm, HF 22mm	934 x 180 x 305mm	18kg

MODEL	RESPONSE	IMPEDANCE	AMPLIFIER	SENSITIVITY	CROSSOVER
A1	55Hz - 25kHz	8 Ohms	25-100watts	84dB	4.2kHz
A2	36Hz - 25kHz	8 Ohms	25-125watts	85dB	4.2kHz
A4	34Hz - 25kHz	8 Ohms	25-150watts	86dB	3.7kHz
A7	32Hz - 25kHz	8 Ohms	25-200watts	88dB	3.7kHz



A1



A2



A4



A7

SPENDOR

Spondor Audio Systems Ltd, G5 Ropemaker Park, South Road, Hailsham, East Sussex BN27 3GY UK
+44 (0)1323 843474 info@spondoraudio.com spondoraudio.com

D-LINE



SPENDOR

MADE FOR MUSIC. DESIGNED FOR YOU.

Our new Spondor D-Line loudspeakers combine cutting-edge research and technical innovation with real-world design. They bring captivating sound quality to the music you love and fit easily and unobtrusively into any setting.

Compatible with all good amplifiers, the floorstanding D7.2 and D9.2 deliver exceptional resolution and low-frequency power, communicating a vibrant realism to music of all genres. With their slim enclosures and smart modern finishes, they're easy to place in dedicated listening rooms or everyday living spaces.

All D-Line loudspeakers draw on our research into cabinet damping, advanced polymers, amplifier-loudspeaker interface, low-frequency airflow and sound behaviour. An inspiring and satisfying choice for audiophiles and discerning music-lovers.

HIGHLIGHTS

- Spondor LPZ high frequency driver
- Fifth Generation Twin-Venturi Linear-Flow port
- New Spondor EP77 Polymer cones
- New Kevlar composite cone low frequency bass drivers
- Spondor Dynamic Damping cabinet technology
- Four elegant natural veneer finishes with premium options
- Multi-Award winning
- Calibrated and matched to broadcast reference standard
- British design and manufacture

TECHNICAL SPECIFICATION

MODEL	DESCRIPTION	DRIVE UNITS	H x W x D	WEIGHT
D7.2	2.5-way floorstanding	2 x LF 180mm, HF 22mm	980 x 192 x 333mm	21kg
D9.2	3-way floorstanding	1 x MF & 2 x LF 180mm, HF 22mm	1155 x 210 x 398mm	35kg

MODEL	RESPONSE	IMPEDANCE	AMPLIFIER	SENSITIVITY	CROSSOVER
D7.2	29Hz - 25kHz	8 Ohms	25-200watts	90dB	900Hz, 3.2kHz
D9.2	27Hz - 25kHz	8 Ohms	25-250watts	90dB	500Hz, 4.2kHz



D7.2



D7.2



D9.2



D9.2

SPENDOR

Spondor Audio Systems Ltd, G5 Ropemaker Park, South Road, Hailsham, East Sussex BN27 3GY UK
 +44 (0)1323 843474 info@spondoraudio.com spondoraudio.com

CLASSIC



Over five decades Spondor Classic loudspeakers have earned iconic status as the reference standard for many audiophiles, musicians and professional sound engineers. Inspired by the enthusiastic world-wide response following the introduction of our flagship Spondor SP200, for 2017 we are introducing the most significant performance improvements ever across all models.

Our new models are built around a totally new generation of Spondor drive units. Featuring advanced polymer and Kevlar cones, cast magnesium alloy chassis, high-efficiency motor systems, optimised electro-dynamic damping and excellent thermal dissipation, they deliver a truly captivating sound with unprecedented transparency and dynamic contrast.

With meticulously refined crossover networks, enhanced cabinet structures, new elastomer panel damping and new style magnetic grilles, the new Spondor Classic loudspeakers deliver music with the captivating warmth and charm of the 70s originals. Refined and perfected over five decades, Spondor Classic offers the ultimate in pure listening pleasure for serious audiophiles.

SPENDOR

MADE FOR MUSIC. DESIGNED FOR YOU.

TECHNICAL SPECIFICATION

- New Spendor EP77 polymer cone drive units
- Bass drivers with Kevlar composite stabiliser domes
- New cabinet design with magnetic grille
- Two elegant natural veneer finishes – Cherry and Dark Walnut
- Calibrated and matched to broadcast reference standard
- British design and manufacture



MODEL	Classic 3/5	Classic 3/1	Classic 2/3	Classic 1/2	Classic 100	Classic 200
DESCRIPTION	2-way sealed shelf mount	2-way reflex stand mount	2-way reflex stand mount	3-way reflex stand mount	3-way reflex stand mount	3-way sealed floorstanding
DRIVE UNITS	LF 150mm, HF 22mm	LF 180mm, HF 22mm	LF 210mm, HF 22mm	LF 210mm, MF 150mm, HF 22mm	LF 300mm, MF 180mm, HF 22mm	2xLF 300mm, MF 180mm, HF 22mm
H x W x D	308 x 165 x 188mm	395 x 220 x 285mm	543 x 273 x 338mm	621 x 308 x 374mm	700 x 370 x 433mm	1117 x 368 x 513mm
WEIGHT	5kg	10kg	15kg	22kg	36kg	55kg
RESPONSE	55Hz – 25kHz	40Hz - 25kHz	35Hz - 25kHz	30Hz – 25kHz	25Hz – 25kHz	20Hz – 25kHz
IMPEDANCE	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms
AMPLIFIER	25-100watts	25-150watts	25-200watts	25-200watts	25-250watts	25-300watts
SENSITIVITY	84dB	88dB	88dB	87dB	89dB	89dB
CROSSOVER	4.2kHz	3.7kHz	3.6kHz	415Hz, 2.7kHz	490Hz, 3.6kHz	550Hz, 3.8kHz

SPENDOR

Spendor Audio Systems Ltd, G5 Ropemaker Park, South Road, Hailsham, East Sussex BN27 3GY UK
 +44 (0)1323 843474 info@spendoraudio.com spendoraudio.com